

Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (Previously Presented) A multilayer mat comprising:
a non-intumescent layer comprising inorganic fibers;
a first intumescent layer forming a first outer layer of the multilayer mat; and
a second intumescent layer forming a second outer layer of the multilayer mat,
wherein the non-intumescent layer is positioned between the first intumescent layer and the second intumescent layer.
2. (Original) The multilayer mat of claim 1, wherein the first intumescent layer and the second intumescent layer each comprise an intumescent material selected from vermiculite, expandable graphite, or combinations thereof.
3. (Original) The multilayer mat of claim 1, wherein the non-intumescent layer has a thickness that is at least 50 percent of a total thickness of the multilayer mat.
4. (Original) The multilayer mat of claim 1, wherein the non-intumescent layer is thicker than the first intumescent layer and the non-intumescent layer is thicker than the second intumescent layer.
5. (Original) The multilayer mat of claim 1, wherein the inorganic fiber comprises a ceramic fiber having a bulk shrinkage no greater than 10 percent.
6. (Original) The multilayer mat of claim 1, wherein the inorganic fibers comprise glass fibers.
7. (Original) The multilayer mat of claim 1, wherein the inorganic fibers comprise glass fibers and both the first and second intumescent layers comprise vermiculite.

8. (Original) The multilayer mat of claim 1, wherein the inorganic fibers comprise a ceramic fiber having a bulk shrinkage no greater than 10 percent and both the first and second intumescent layers comprise vermiculite.
9. (Original) The multilayer mat of claim 1, wherein two or more layers of the multilayer mat are bonded together with an adhesive, needle bonding, or stitching.
10. (Currently Amended) A pollution control device comprising:
a first metal housing;
a pollution control element inside the first metal housing;
a multilayer mounting mat positioned between the first metal housing and the pollution control element, said multilayer mounting mat comprising:
a non-intumescent layer comprising inorganic fibers;
a first intumescent layer forming a first outer layer of the multilayer mat; and
a second intumescent layer forming a second outer layer of the multilayer mat,
wherein the non-intumescent layer is positioned between the first intumescent layer and the second intumescent layer.
11. (Original) The pollution control device of claim 10, further comprising a second metal housing surrounding the first metal housing, wherein an exhaust gas passes between the first metal housing and the second metal housing.
12. (Original) The pollution control device of claim 10, wherein the non-intumescent layer has a thickness that is at least 50 percent of the total thickness of the multilayer mat.
13. (Original) The pollution control device of claim 10, wherein the non-intumescent layer is thicker than the first intumescent layer and the non-intumescent layer is thicker than the second intumescent layer.

14. (Original) The pollution control device of claim 10, wherein the inorganic fibers comprise ceramic fibers having a bulk shrinkage less than 10 percent.
15. (Original) The pollution control device of claim 10, wherein the inorganic fibers comprise glass fibers.
16. (Original) The pollution control device of claim 10, wherein the inorganic fibers comprise glass fibers and both the first and second intumescent layers comprise vermiculite.
17. (Canceled)
18. (Previously Presented) The pollution control device of claim 11, wherein the pollution control element is a diesel particulate filter.
19. (Original) The pollution control device of claim 10, wherein the mounting mat has sufficient holding pressure at operating temperatures both higher than and lower than a temperature suitable for expanding the first and second intumescent layers.
20. (Withdrawn) A method of forming the multilayer layer mat of claim 1, wherein said method comprises:
- providing a non-intumescent layer comprising inorganic fibers;
 - positioning a first intumescent layer so as to form a first outer layer of the multilayer mat;
 - positioning a second intumescent layer so as to form a second outer layer of the multilayer mat; and
 - positioning the non-intumescent layer between the first intumescent layer and the second intumescent layer.
21. (Previously Presented) The pollution control device of claim 11, wherein the pollution control element is a catalytic converter element and the pollution control device is a catalytic converter.